



Tape	Description	Tensile	Adhesion to Stainless Steel	Thickness	Holding Power to Fiberboard	Service Temperature Range
HP 100	Automated or manual sealing of lightweight cartons <ul style="list-style-type: none"> • Easy unwind • Instant, permanent bond • Application temperature range of 35F to 110F 	21 lbs/in width	43 oz/in width	1.6 mils	10,000 min	20-150F
HP 200	Automated or manual sealing of medium-weight cartons <ul style="list-style-type: none"> • Superior performance • Instant, permanent bond • Transparent colors for inventory identification • Application temperature range of 35F to 110F 	27 lbs/in width	44 oz/in width	1.9 mils	15,000 min	20-150F
HP 300	Automated or manual sealing of medium-weight cartons <ul style="list-style-type: none"> • Performance grade • Instant, permanent bond • Application temperature range of 35F to 110F 	30 lbs/in width	47 oz/in width	2.2 mils	20,000 min	20-150F

<p>HP 400</p>	<p>Automated or manual sealing of large, heavyweight cartons</p> <ul style="list-style-type: none"> • High performance • Instant, permanent bond • Ideal for high-speed, critical-closure production lines • Application temperature range of 35F to 110F 	<p>33 lbs/in width</p>	<p>54 oz/in width</p>	<p>2.5 mils</p>	<p>25,000 min</p>	<p>20-150F</p>
<p>HP 500</p>	<p>Automated or manual sealing of heavy duty cartons</p> <ul style="list-style-type: none"> • Premium grade • Instant, permanent bond • Ideal for use on demanding packaging lines on cartons • Application temperature range of 35F to 110F 	<p>42 lbs/in width</p>	<p>58 oz/in width</p>	<p>3 mils</p>	<p>30,000 min</p>	<p>20-150F</p>
<p>HP 800</p>	<p>Automated or manual bottom sealing of heavy duty, double and tripple walled cartons</p> <ul style="list-style-type: none"> • Abrasion resistant polyester film • Meets ASTM D5486, Type II standard • Application temperature range of 35F to 110F 	<p>54 lbs/in width</p>	<p>95 oz/in width</p>	<p>3.4 mils</p>	<p>35,000 min</p>	<p>20-150F</p>